This package includes: 304 Stainless Steel frame and headers, (2) End Suction pumps, ball valves with quick removal unions, s.s. pump discharge checks, 4.6" STN Mono-Chrome Touch-Screen with alarm log NEMA 1 controller with circuit breakers on primary and secondary circuits, EEPROM PLC controller, H-O-A switches on each pupm, control power switch, main disconnect, common trouble alarm (Low Suction, High System), micro VFD's with full PID control and intelligent thermal shutdown.

Package System Selection Chart

Refer to the chart below to determine the flow rate and boost pressure is required for EACH pump
Find the GPM on the left and follow to the right to determine the pump NET boost pressure
Find the associated model number and refer to the pricing chart below to determine the price.

	PSI				
GPM	**20**	**25**	**30**	**40**	**50**
50		P25-1	P25-1	P25-2	P25-3
70	P25-2	P25-2	P50-2	P25-3	P25-3
90	P50-3	P50-3	P50-3	P50-3	P50-5
110	P50-3	P50-3	P50-3	P50-5	P50-5
130	P50-3	P50-3	P50-5	P50-5	
150	P50-5	P50-5	P50-5	P50-5	

Model	Pump Type	Horsepower	Voltage
P25-1	125M	1.5	208/460
P25-2	125M	2	208/460
P25-3	125M	3	208/460
P50-2	150M	2	208/460
P50-3	150M	3	208/460
P50-5	150M	5	208/460

Part Number Breakdown

P25 - X

P25 → 25 = 125M, 50 = 150M

X → HP

Standard 1 Year factory parts warranty against materials and workmanship applies.
* Refer to factory for current discount multipliers.